

300 OIL

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT: NATIONAL 300 REFRIGERATION OIL

PRODUCT CODE: 300 OIL

CHEMICAL NAME/FAMILY: MINERAL OIL

MANUFACTURER: NATIONAL REFRIGERANTS, INC. **ADDRESS:** 11401 Roosevelt Boulevard Phila., Pa. 19154

INFORMATION: 800-262-0012 **EMERGENCY:** 800-424-9300 **PREPARER:** Matt Callahan

2. HAZARD IDENTIFICATION

CLASSIFICATION: Not classified according to 29 CFR 1910.1200 (2012)

OTHER HAZARDS: SKIN AND EYE CONTACT: Prolonged contact may cause minor skin

irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTCAS#WEIGHTDistillates, (petroleum), hydrotreated heavy naphthenic64742-52-7100%

*no hazardous ingredients

COMMON NAMES AND SYNONYMS

Mineral Oil

There are no stabilizers or impurities that contribute to the classification of the material identified in section 2

4. FIRST AID MEASURES

EYES: Flush with large amounts of water for at least 15 minutes. If redness or irritation persists, contact a physician.

SKIN CONTACT: Wash with soap and water.

INHALATION: None normally required.

INGESTION: Call a physician.

Page 1 of 4

300 OIL

Current Issue Date: April 2015



300 OIL

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, CO2, foam, waterfog, sand/earth

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus. Water spray is an unsuitable extinguishing agent.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: Stop leak. Dike up large spills. Use inert absorbent materials such as earth, sand or vermiculite for clean-up. Use personal protective equipment such as gloves, goggles, and coveralls to prevent contact with skin during clean up.

7. HANDLING AND STORAGE

PRECAUTIONS FOR STORAGE AND HANDLING: Avoid exposure to heat and flames. Protect against eye and skin contact. Store containers in an upright and secure position to prevent spills and protect against damage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Provide adequate ventilation when working in confined areas

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:

General work clothing and gloves (leather) should provide adequate protection. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION:

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL use a NIOSH approved respirator.

ADDITIONAL RECOMMENDATIONS:

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn.

Page 2 of 4

300 OIL



300 OIL

EXPOSURE LIMITS

OSHA permissible concentration of mineral oil mist in air is 5 mg/m3.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear amber liquid ODOR: Petroleum odor ODOR THRESHOLD: Not determined

PH: Neutral
MELTING/FREEZING POINT: O°C (32F°)
BOILING POINT: >500°F

FLASH POINT: Closed cup: 98 to 344°C (208.4 to 651.2°F)

Open cup: 185°C (365°F) [Cleveland.]

EVAPORATION RATE: Negligible FLAMMABILITY: Not applicable LEL/UEL: Not applicable

VAPOR PRESSURE: <0.011 kPa (<0.08mmHg) at 25°C

VAPOR DENSITY: >10 (air=1) RELATIVE DENSITY: 0.916

SOLUBILITY: Insoluble in water

PARTITION COEFFICIENT

n-Octanol/water: 2 - 6

AUTO IGNITION TEMPERATURE: Not determined DECOMPOSITION TEMPERATURE: Not determined

VISCOSITY: $61.43 \text{ cSt} (40^{\circ}\text{C} (104^{\circ}\text{F}))$

10. STABILITY AND REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: NONE

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents such as chromic

acid, hydrogen peroxide and bromine.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Upon combustion, CO2 and CO

are generated.

11. TOXICOLOGICAL INFORMATION

INHALATION AND SKIN ABSORPTION HEALTH RISKS: OSHA permissible

concentration of mineral oil mist in air is 5 mg/m3.

SKIN AND EYE CONTACT: Prolonged contact may cause minor skin irritation.

Page 3 of 4

300 OIL

Current Issue Date: April 2015



300 OIL

SYMPTOMS OF EXPOSURE: N/A

INGESTION: N/A

ACUTE AND CHRONIC HEALTH HAZARDS: N/A

CARCINOGENICITY: NTP IARC MONOGRAPHS OSHA REGULATED

NO NO NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State, and Local regulations.

14. TRANSPORATION INFORMATION

US DOT ID NUMBER: None
US DOT PROPER SHIPPING NAME: None
US DOT HAZARD CLASS: None
US DOT PACKING GROUP: None

15. REGULATORY INFORMATION

This material is not a hazardous waste under RCRA Regulation 40 CFR 261.

16. OTHER INFORMATION

HMIS: H F R

DISCLAIMER

INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION. NO WARRANTY IS MADE CONCERNING THE ACCURACY AND NO LIABILITY SHALL BE MADE FOR CLAIMS FOR USE OR RELIANCE OF THE RECOMMENDATIONS CONTAINED HEREIN.

Page 4 of 4

300 OIL

Current Issue Date: April 2015